

Steel Fan & Fixture Box Kits for Suspended Ceilings

Plated steel fan/fixture box with adjustable mounting bar. For mounting a fan or fixture on a suspended ceiling grid. FS420SCL and FS427SCL for fixtures only.

CATALOG NUMBER	UPC/DCI/NAED MFG #018997	DESCRIPTION / CU. IN.	UNIT PKG	STD PKG	DIM A	DIM B	DIM C
FBR5420SC*	75300	For suspended ceilings 2" box depth 20.0 cu. in.	1	5	4.224	5.500	24.000
FS420SCL	12526	For suspended ceilings 2" box depth 20.0 cu. in.	1	10	3.041	3.500	25.000
FS427SCL	12537	For suspended ceilings 2-1/8" box depth 30.0 cu. in.	1	10	3.222	3.500	24.000



PATENTED.

Note: Install fan or fixture (not included) in accordance with manufacturer's instructions and all local applicable electrical codes, using the parked screws provided. *Packaged with Wire Grabber™ Kit on page S-4 Refer to chart on page R-25 for load ratings and number of single conductors.

FEATURES AND BENEFITS

- Ships fully assembled
- Comes preset for a 24" grid
- Installs quickly and securely, saves 30 minutes of installation time
- No parts to lose, installation and adjustment screws ship parked in place
- FBR5420SC features breakable mounting clips to lower box position for ceiling tiles that extend below the grid
- FBR5420SC has parked fan/fixture installation screws ready for easy fan/fixture bracket installation!
- FBR5420SC is UL rated: 70 lb fan, 70 lb fixture; CSA rated: 50 lb fan/fixture
- FS420SCL is UL and CSA rated: 50 lb fixture
- FS427SCL is UL and CSA rated: 50 lb fixture
- Listed for use in environmental air handling spaces per NEC code requirements 300.25(c)

INSTALLATION INSTRUCTIONS for FBR5420SC




Installation with FL430 is even faster and it costs less than our FS420SCL fixture box with adjustable bracket.

- 1) Cut a 4-1/16" diameter hole in the center of a 24" ceiling tile. Place box over hole. Snap ends of support bar over the ceiling grid.
- 2) Pull cable through installed NM cable connector and remove captive screws for fan/fixture bracket installation.



Now with WireGrabber™ kit for drop wire support of static loads.

FBR5420SC Installation Option



To Mount Box Off Center: Loosen screws and slide box into position.