

# 2711



**Color :**  Black-White

**UPC Code :** 078477808351

**Country Of Origin :** Mexico

**NEMA :**  L14-30P

**Available Colors :**



Black

Locking Plug, 30 Amp, 125/250 Volt, Industrial Grade, Black & White

30 Amp, 125/250 Volt, NEMA L14-30P, 3P, 4W, Locking Plug, Industrial Grade, Grounding - Black/White

**ROHS Compliant :** Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes (.245"-.700")
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty
- Ideal for generators and transfer switches

## Technical Information

### Electrical Specifications

**Amperage :** 30 A

**Current Interrupting :** Certified for current interrupting at full rated current

**Dielectric Voltage :**  
Withstands 2000V per UL498

**Grounding :** Grounding

**Pole :** 3

**Temperature Rise :** Max 30C after 250 cycles OL at 200 percent rated current

**Voltage :** 125/250 VAC

**Wire :** 4

### Environmental Specifications

**Environment :** Dry

**Flammability :** Rated HB or better UL94

**Operating Temperature :** -40° C to 60°C

### Material Specifications

**Assembly Screws :** Steel, Zinc Plated

**Back Cover :** Thermoplastic

**Blades/Contacts :** Solid Brass

**Body Material :** Impact Modified Nylon

**Clamp Insert :** Nylon

**Color :** Black-White

### Mechanical Specifications

**At Rated Voltage :** 2 HP L-L / 2 HP L-N

**Cord Range :** 0.560 to 1.050

**Product ID :** Ratings are permanently marked on device

**Terminal Accom. :** 14-8 AWG

**Terminal ID :** Brass-Hot, Green-Ground, Silver-Neutral

**Torque Range :** 10-14 in-lbs

**Cord-Clamp** : Nylon

**Terminal Screws** : Brass

**Wire Module** : Nylon

Product Features

**Brand** : Black and White

**Color** : Black-White

**Device Type** : Locking Plug

**NEMA** : L14-30P

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File LR-406

**NEMA** : WD-6

**NOM** : 057

**UL Fed Spec WC-596** : File E13393

**UL498** : File E13393

**Warranty** : Limited Lifetime Warranty

**SPECIFICATION SUBMITTAL**

|                                            |                                                 |                      |
|--------------------------------------------|-------------------------------------------------|----------------------|
| <b>JOB NAME:</b><br><input type="text"/>   | <b>CATALOG NUMBERS:</b><br><input type="text"/> | <input type="text"/> |
| <b>JOB NUMBER:</b><br><input type="text"/> | <input type="text"/>                            | <input type="text"/> |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-461-2002 ·  
FAX: +1-800-824-3005 ·

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 ·

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2026 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without  
notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/company/about-leviton/locations](http://www.leviton.com/company/about-leviton/locations)

© 2026 Leviton Manufacturing Co., Inc.