



Project/Job Name:

Location:

Fixture Type:

Notes:

S11835R1 - 9 Watt; LED Downlight Retrofit; 5-6 Inch; CCT Selectable; 120 Volts; Black Finish

- Air Tight
- IC Rated
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	120V
Lumens:	800L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase cut
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Connector or Adapter
THD:	<45%
Power Factor :	>0.9
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923711886
Each Quantity:	1
Each Dimensions:	7.60 x 2.36 x 8.46

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Plastic (PS)
Dimensions:	H:2.31" DIA:7.41"
Weight (Lbs.):	0.68
Material:	Steel

INSTALLATION

Ceiling Aperture:	5.875 in. Cutout
Clearance Height:	3.25
Sloped Ceiling Compatible:	No
Can Size:	5-6 in.

COMPLIANCE

Safety Listing:	cETLus - Classified
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	3354720
Energy Star Lamp Category:	Downlight Solid State Retrofit
DLC Approved:	No
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-2676	Pressure Bracket kit for 5/6-Inch Downlight Retrofits, set of two brackets
--	----------------	--

	80-868	QC to E26 Socket Whip for Downlight Cans; Temp Light Adapter Cable
--	---------------	--

	80-982	5 Inch Recessed Can; For New Construction
--	---------------	---

	80-983	5 Inch Recessed Can; For Remodeling
--	---------------	-------------------------------------

	80-988	6 Inch Recessed Can; For New Construction
--	---------------	---

	80-989	6 Inch Recessed Can; For Remodeling
--	---------------	-------------------------------------

	80-996	DLR Air Tight Foam Gasket; White Finish; 12-Pack
---	---------------	--

	S12621	Friction Band for 5/6 Inch Downlight Retrofit; Adapter for Oversized Can
---	---------------	--

	S8999	GU24 Socket Adapter For Recessed Down Light
--	--------------	---

	S9000	GU10 Socket Adapter For Recessed Down Light
--	--------------	---



S11835R1 - 9 Watt; LED Downlight Retrofit; 5-6 Inch; CCT Selectable; 120 Volts; Black Finish

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Leviton	66DF-10W
Satco	86/103
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSE06-10Z
Leviton	DSL06
Leviton	DSM10
Eaton	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVCL-253P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQRA-PRO
Lutron	HQRD-10D
Lutron	HQRD-10NBD
Lutron	HQRD-6CL

Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL
Lutron	HQRD-PRO
Lutron	HRST-PRO-N
Leviton	IPLo6
Lutron	LECL-153P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MAELV-600
Precision	MR42400PLS
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Overdrive	ODMR0205
Lutron	PD-10NXD
Lutron	PD-5NE
Lutron	PD-6WCL
Lutron	PHPM-WBX-120
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-10D
Lutron	RRD-6CL
Lutron	RRD-6ND
Lutron	RRD-H6BRL

Lutron	RRD-PRO
Lutron	RRST-PRO-N
Satco	S11268
Eaton	SAL06P
Lutron	SCL-153P
Lutron	SELV-300P
Lutron	ST-PRO-N
Lutron	STCL-153M
Eaton	SUF7
Eaton	TAL06P-C2
Lutron	TGCL-153PH
Leviton	TSL06
Leviton	TSM10
Lutron	TTCL-100H
Eaton	VSUL06D
Acuity	WSX-PDT-WH
Legrand	WWRL50WH