

SLIM FIT - CCT SELECTABLE



- High efficacy, up to 89 lumens per watt (LPW)
- 50,000 hours functional life (L70)
- Ambient operating temperature: -4°F to 104°F
- Ultra-thin white aluminum die-cast construction
- Acrylic lens
- Recessed housing not required, remote J-box provides flexibility in mounting

Catalog Number	Order Code	Max Lumens	Wattage	Input Voltage	CCT	Minimum CRI	Beam Angle	Trim Style	Size	Incandescent Replacement Wattage	ENERGY STAR	T24 JAB
Round												
RDL/3RND/8/5CTS	71084	530	8W	120V	Selectable	90	110°	Smooth	3"	50W	Y	Y
RDL/4RND/9/5CTS	70885	550	9W	120V	Selectable	90	110°	Smooth	4"	60W	Y	Y
RDL/6RND/12/5CTS	70886	850	12W	120V	Selectable	90	110°	Smooth	6"	75W	Y	Y
RDL/6RND/12HL/5CTS	70887	1,050	12W	120V	Selectable	90	110°	Smooth	6"	100W	Y	Y
RDL/8RND/18/5CTS	71085	1,600	18W	120V	Selectable	90	110°	Smooth	8"	100W	Y	Y
Gimbal												
RDL/4GIM/9/5CTS-46	70888	580	9W	120V	Selectable	90	100°	Smooth	4"	50W	Y	Y
RDL/4GIM/11/5CTS-46	70889	770	11W	120V	Selectable	90	100°	Smooth	4"	65W	Y	Y
RDL/4GIM/15/5CTS-46	70890	1,000	15W	120V	Selectable	90	100°	Smooth	4"	75W	Y	Y
RDL/6GIM/16/5CTS-46	72788	1,200	16W	120V	Selectable	90	100°	Smooth	6"	85W	Y	Y
Square												
RDL/4SQ/9/5CTS-46	71130	570	9W	120V	Selectable	90	110°	Smooth	4"	50W	Y	Y
RDL/6SQ/11/5CTS-46	71134	770	11W	120V	Selectable	90	110°	Smooth	6"	65W	Y	Y
RDL/6SQ/15/5CTS-46	71135	1,000	15W	120V	Selectable	90	110°	Smooth	6"	75W	Y	Y

Accessories (Sold Separately)

Catalog Number	Order Code	Description
RDL/CBL/5CTS/6FT-97	70880	6' Low Voltage Extension Cable for use with 4", 6" and 8" Round
RDL/CBL/5CTS/6FT-46	71090	6' Low Voltage Extension Cable for use with 3" Round, Gimbal or Square
RDL4-FRAME KIT	77223	4" Frame-In Kit
RDL6-FRAME KIT	77225	6" Frame-In Kit



(Frame-In Kit)



(6' Low Voltage Extension Cable)

